

MASK WITH GUSSET

This invention relates generally to masks for use in respiratory therapy. One use is in CPAP treatment of Obstructive Sleep Apnea. However, the mask arrangements presented
5 herein are useful in other types of respiratory therapy. In the quest for an improved mask arrangement for respiratory therapy, there are various design objectives – effectiveness of seal between the mask and the patient’s face, good compliance with a prescribed therapy regime, and patient comfort. The present invention provides various embodiments of a novel mask arrangement, which offers several distinct advantages over known mask arrangements.

BACKGROUND

In respiratory therapy where air is delivered to the mask under pressure, it is important to maintain a good seal between the mask and the patient’s face. Leaks between the mask and the patient’s face can reduce the desired air pressure in the mask and create
10 increased noise. Both can reduce the effectiveness of, and compliance with, the therapy. In the first instance, the prescribed treatment parameters are not being maintained. In the latter, the increased noise can disrupt the sleep cycle of both the patient and the patient’s bed partner.

Leaks are especially prone to occur as the patient moves during the night. Drag and
20 movement of the air delivery tube or the mask system as the patient turns or moves can alter the positioning and alignment of the mask with respect to the patient’s face, which movement can be translated or transferred to the cushion seal, creating leaks. Thus, while the mask may initially be leak free when attached to the patient, leaks are prone to develop later in the night as the patient moves in bed, awakening the patient. Hence, patients may tighten straps more

than is necessary for pressure requirements in order to reduce or prevent leaks that result from movement.

Many different mask systems are known. One broad group of known mask systems include a rigid shell, a face-contacting cushion and headgear. The shell typically encompasses the nose or nose and mouth. Some known shells encompass the entire face. The cushion is typically constructed from a soft material such as silicone. A headgear provides a means to secure the mask in position. One known form of headgear consists of an arrangement of straps.

Certain mask designs have been developed to increase the flexibility of the mask cushion to enhance patient comfort while maintaining an effective seal between the mask and the patient. The Bubble Cushion (a registered trademark of ResMed, Ltd.) Mask, covered by US Patent No. 5,243,971, the subject matter of which is incorporated herein by reference, uses a flexible cushion membrane attached to a mask shell and the pressure inside the mask system to assist in the seal of the cushion membrane itself against the skin or face of the user.

The ResMed Mirage (a registered trademark of ResMed, Ltd.) Mask System, is covered by, inter alia, US Patent No. 6,112,746, the subject matter of which is incorporated herein by reference, has a contoured, three-dimensionally shaped cushion having an outer face-contacting membrane spaced apart from an inner frame rim to both assist in the seal and increase the comfort of the patient. Neither of these masks incorporates an expanded gusset section for mounting the cushion to the mask to assist in sealing the mask to the patient (user).

A known fitting procedure with a known mask has been to supply the maximum air pressure to the mask that will be supplied to the mask during the therapy and to adjust the strap tension to the necessary level to prevent leaks at that maximum air pressure. However, in many therapy regimens, this maximum air pressure is often encountered only during a

portion of the duration of the therapy and the mask air pressure is lower at other times during the therapy. Such is the case, for example, when using auto-titrating or variable pressure systems or during ramp-up when using CPAP systems. Thus, the strap tension is higher than necessary during significant portions of the therapy duration. Further, since leaks are
5 disruptive of both the sleeping cycle and the prescribed therapy regimen, patients will often tighten the straps even more than is necessary to prevent leaks at the maximum encountered air pressure. In known masks, this higher than necessary strap pressure directly results in a higher than necessary force of the mask cushion on the patient's face, particularly as the pressure goes below the maximum mask air pressure.

10 See Figure 1, which shows a force diagram for a known mask 110 having a cushion 130 attached to a rigid shell 120. The cushion 130 includes a face-contacting portion 134 attached to a cushion sidewall 173. The cushion sidewall 173 can be relatively flexible, as in the ResMed Bubble Cushion® mask, or relatively rigid, as in the ResMed Mirage® mask. Although the mask 110 would be in contact with the face 42 of a patient 40 (shown in
15 phantom) in use, for purposes of clarity in this diagram (as well as the diagram of Figure 10), a flat foundation 43 is substituted for the patient's face 40. The total force of prior art masks on the user's face F_m has been found empirically to be given by the equation $F_m = F_c + F_{Ac}$, where F_c is the force of the cushion on the patient's face and F_{Ac} is the force on the patient's face of the mask air pressure P inside of the perimeter of A_c , the area of contact of the
20 cushion with the patient's face. The force F_{Ac} is given by the equation $F_{Ac} = PA_c$. Since the force F_c is distributed around A_c and is not merely located at two points on the cushion, as it might seem due to the limitations of the two-dimensional representation of Figure 1, this force is shown in parentheses. Although A_c is shown inward of the sidewall 173 as would be the case if the mask 110 had just been brought into contact with the user's face with a
25 minimal contacting force, in practice, the face-contacting portion 134 tends to roll under

when sufficient force is applied to the mask 110 to seal the mask to the user's face such that A_c can expand outward, toward the sidewall 173.

The force (tension) in the headgear strap F_s for the prior art mask has been found empirically to be given by the equation $F_s = (F_c + F_{Ac})/(2\cos\theta)$, where θ is the angle of the head strap with respect to the mask 110. Thus, the force of the cushion on the patient's face F_c is given by the equation $F_c = 2F_s\cos\theta - F_{Ac}$. The force of the mask cushion on the patient's face is difficult to distribute completely evenly around the cushion in known masks, especially at higher forces, and results in localized high pressure spots around the mask cushion. This higher force on the face, and especially the localized high pressure spots, are uncomfortable to the patient and can disrupt the sleep cycle. See, for instance, Figure 2, which charts the force required to secure a mask on a face versus the air pressure in the mask (measured in centimeters H_2O). As seen there, the force required to maintain a known mask sealed to the face throughout a mask air pressure range is most substantially affected by the maximum air pressure in the mask that will occur during therapy. That is, the force of the mask on the face remains at a fairly high level even when the pressure in the mask drops and this force of the mask on the face is directly related to the force necessary to seal the mask at the maximum mask air pressure. Misalignment of the mask will move the curve upward as higher forces are required to seal the mask to the face in light of the misalignment.

This force on the face increases as the head straps of a known mask are tightened to increase the sealing force of the mask, and thereby compressing the cushion and bringing the shell of the mask closer to the patient's face. When the straps are tightened, the shell of the mask moves a distance X between a position X_0 when a seal is first obtained to a position X_p when it reaches the point where the cushion is being compressed beyond its normal range. The mask shell may be able to move beyond X_p but the cushion tends to become rigid or nearly so at about X_p , thereby limiting further travel. In a known mask, F_c generally increases

at a first rate (i.e., the slope of the curve) as the mask moves toward the patient's face within a given range of X. This first rate occurs within the range of flexibility of the face-contacting portion 134. This first rate is also a function of the pressure in the mask acting on a back side of the face-contacting portion 134 of the mask. Thus, as the pressure in the mask increases,
5 the first rate also increases within the given range of X.

However, the known cushion becomes less flexible as it is further compressed beyond such range of X. In a mask having a more flexible sidewall, as discussed above, F_c will then increase at a faster rate as the mask moves toward the patient's face due to a spring-force imparted by the sidewall until such point as the sidewall is nearly completely compressed and directly passing on the force from the rigid mask shell to the face. In a mask having a more
10 rigid sidewall, as discussed above, F_c will then increase at an even faster rate for a short distance as the mask moves toward the patient's face but will quickly reach a point where the rigid sidewall is directly passing on the force from the rigid mask shell to the face.

See Figure 3, which charts the force required to secure a mask on a face versus the movement of the mask frame (shell) from a relaxed positioned toward the face. The solid
15 curve of Figure 3 shows the force on the face for a known mask, such as the ResMed Mirage® mask, at a mask air pressure of 10 cms H₂O. It can be seen from this curve that the force on the face increases in generally linear proportion to the movement of the mask towards the face within the range of flexibility the cushion 130. However, at such point
20 where the cushion is nearly completely compressed (at approximately 5-7 mm in Figure 3) so that the generally rigid sidewalls of the cushion 130 begin directly transferring the force from the rigid shell 120 to the face, the force on the face increases dramatically as the mask shell moves toward the face.

U.S. Patent Nos. 5,492,116 and 5,655,527 to Scarberry disclose a full-face respiratory
25 mask. The mask includes a flexible seal member 18 directly attached to a mask shell 12 and

is attached to the user's head by head gear 24. The flexible seal member 18 itself contacts the user's face with a broad area of contact and maintains a seal with the user's face through pressure in the space 62 acting directly upon seal membrane inner surface 54.

Japanese Provisional unexamined patent application (Laid-open Kokai) published
5 January 6, 1999 entitled NASAL MASK FOR RESPIRATION, Provisional Publication No. 11-397 discloses a bellows-formed elastic body between a mask shell and cushion. As seen in the figures of that publication, the bellows portion of the mask projects an area over the patient's face that is substantially the same as the contact area defined by the line of contact of the mask cushion with the patient's face. This publication teaches nothing about the
10 relationship between the area of the bellows and the force applied to the patient's face.

Although the bellows provides limited mechanical flexibility, no significant pressure
15 advantages or significant mechanical flexibility can be achieved. This mask does not overcome the sealing problems incurred by movement of the mask with respect to the patient's face without utilizing an increased head strap pressure across the mask air pressure operating range.

SUMMARY OF THE INVENTION

In one aspect, the invention provides a mask system including a shell which in use is positioned in a predetermined position relative to a patient's face, a face-contacting cushion
20 which in use transfers a force to the patient's face, and a means for permitting relative movement between the cushion and the shell wherein said means provides a predetermined force on the cushion. In one form, the predetermined force is a function of mask pressure. In another form, the predetermined force is a function of the displacement of the shell relative to the face. In another form, the predetermined force is a function of both mask pressure and
25 displacement of the shell relative to the face. In another form, the predetermined force is

independently controlled. In another form, the means for permitting relative movement between the cushion and the shell is provided by a gusset section positioned in-between the shell and the cushion.

In one aspect, the invention provides a mask system including a face-contacting cushion having a first projected area on the face, a mask shell and a gusset section therebetween, the gusset section having a second projected area on the face wherein the second projected area is greater than the first projected area by greater than approximately 30%.

In another aspect the invention provides a mask system for use at a mask pressure including headgear coupled to a shell which exerts forces on the shell and a face-contacting cushion which transfers forces to the face, constructed and arranged so that the force transferred from the face-contacting cushion to the face is a strong function of mask pressure. The greater projected area of the gusset arrangement with respect to the face contacting area of the cushion uses the air pressure in the mask to expand the gusset into contact with the patient's face, even when the mask shell changes alignment with the patient's face, to provide a more secure seal between the mask and the patient. The expansion, contraction and bending of the gusset allows for enhanced mechanical flexibility over known mask arrangements that helps to maintain a seal even when the patient moves significantly during sleep and the position of the mask with respect to the patient's face changes. Thus, the force of the mask on the face is most significantly proportional to the mask air pressure and the cushion is maintained in secure sealing contact with the patient's face by the mask air pressure over a broader range of positioning of the mask with respect to the patient. This allows for the tension in the straps of the headgear to be generally less than with a known mask to securely seal the mask to the patient's face, especially at mask air pressures below the maximum mask

air pressure for the therapy, providing greater patient comfort and compliance with the prescribed respiration therapy regime.

While some membrane-type cushion mask arrangements accommodate limited relative movement between the cushion and the wearer's face while maintaining a tolerable seal, the present invention dramatically increases the level of accommodation without a corresponding increase in the head strap pressure used to secure the mask to the patient. The gusset section provides a flexible component between the mask shell and the cushion in contact with the user's face while reducing the tension required in the headgear to maintain the seal.

Other embodiments of the present invention provide new mask cushion configurations that assist in maintaining the seal between the mask cushion and the user's face.

Another embodiment of the present invention includes the use of a novel baffle element positioned within the interior space of the mask arrangement. The employment of a baffle member within the mask of the present invention minimizes short-circuiting of the intake gas directly to the exhaust vent with the resulting buildup of carbon dioxide. Thus, the baffle serves to reduce the functional dead space of the mask and reduce the level of carbon dioxide rebreathing by the patient.

With the foregoing in mind, other objects, features and advantages of the present invention will become more apparent upon consideration of the following description and the appended claims with reference to the accompanying drawings, all of which form part of this specification, wherein like reference numerals designate corresponding parts in various figures.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a force diagram for a known mask;

Figure 2 charts the force required to secure both known and present invention masks on a patient's face versus the air pressure in the mask;

Figure 3 charts the force required to secure both known and present invention masks on a patient's face versus the movement of the mask shell from a relaxed positioned toward
5 the patient's face;

Figure 4 shows a side elevational view of a mask of the present invention;

Figure 5 shows a perspective view of the mask of Figure 4;

Figures 6-7 are partial sectional views of the gusset portion of the mask of Figure 4 before and after inflation;

10 Figure 8 is an end elevational view of a mask shell side of the gusset portion of the mask of Figure 4;

Figure 9 is a partial sectional view of the cushion of the mask of Figure 4;

Figure 10 shows a force diagram of the mask of Figure 4;

15 Figure 11 is a perspective view of a mask of the present invention attached to a patient using strap-based headgear;

20 Figure 12 is a partial sectional view of an alternative embodiment of the gusset portion of the present invention;

Figure 13 is a partial side elevational view of an alternative embodiment of the gusset portion of the present invention;

25 Figure 14 is a partial sectional view of an alternative embodiment of the gusset portion of the present invention;

Figures 15-18 show sectional views of alternative embodiments of the mask of the present invention in contact with a patient's face;

Figure 19 diagrams the key characteristics, principal advantages and patient benefits deriving from the present invention and leading to increased therapy compliance by the patient;

Figure 20 shows an elevational view of the interior of the mask shell of one
5 embodiment of the present invention;

Figure 21 shows a diagrammatic view of an alternative embodiment of the present invention;

Figure 22 shows a diagrammatic view of an alternative of the embodiment shown in Figure 21;

10 Figure 23 shows a partial sectional view of one alternative of the embodiment of Figure 21;

Figure 24 shows a partial sectional view of another alternative of the embodiment of Figure 21; and

Figures 25-30 show partial sectional views of alternative embodiments of a mask cushion of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

*Perf
PB*
20 A first embodiment of the respiratory mask 10 of the present invention is shown in Figures 4-9. The mask 10 includes a generally rigid shell 20 having an air tube 22 for connecting to a pressurized air supply 23. A gusset portion 32 is attached to the shell 20 in a known manner such as gluing or mechanical fastening. The gusset portion 32 acts as a suspension mechanism for a cushion 30 and includes a flexible gusset sidewall 33. A partial sectional view of the gusset portion 32 is shown in Figure 6. In this embodiment, the gusset
25 sidewall 33 has a generally uniform thickness and the gusset portion 32 has a generally

5 triangular cross-section when not exposed to mask pressure. However, in this embodiment, the flexible sidewall 33 will balloon out when the mask 10 is pressurized to take on the more rounded cross-section shown in Figure 7. The Figure 8 end view of the gusset portion 32 shows that the gusset has a generally triangular outline to conform with the shape of the cushion 30 and shell 20.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
222

that it utilizes the pressure in the mask acting on its increased surface area to provide the primary force for maintaining the face-contacting portion of the cushion in sealing contact with the user's face. The second key characteristic of the gusset portion is that it provides a decoupling joint between the face-contacting portion 34 of the cushion 30 and the mask shell 20, thus allowing some relative movement between the mask and the user's face. This arrangement substantially protects the seal from undue disturbance in the following scenarios: 1) displacement or tilting of mask shell or harness; 2) relaxation of the facial muscles; 3) movement of the patient; and/or 4) movement of the tube. Figure 11 shows one embodiment of the mask of the present invention attached to a patient.

Figure 10 shows a force diagram representative of the mask embodiment shown in Figures 4-9 (as well as various alternative embodiments of the present invention discussed below). Figure 10 shows A_c , the area of contact of the cushion with the patient's face and A_g , the area defined by the gusset portion 32, for the present invention mask.

The area A_g is a projected area on the user's face (i.e., projected on a plane normal to an axis of the mask) of an interior of the gusset portion 32 exposed to the mask air pressure. In the embodiment shown in Figures 4-10, A_g extends to the outermost interior surface of the sidewall 33 of the gusset portion 32 and includes A_c . As can be seen, the addition of the gusset portion 32 to the mask 10 results in an area A_g being significantly greater with respect to the area A_c than is found in either the prior ResMed® masks (see Figure 1) or the mask disclosed in Japanese Provisional Publication No. 11-397, discussed above.

The significance of this can be seen from the following. In one form of the invention, the total force of the mask on the face F_m is given by the empirical equation $F_m = F_c + F_{Ac} = P(A_g - kX) = 2F_s \cos \theta$. The force of the cushion on the patient's face F_c is given by the empirical equation $F_c = P(A_g - A_c - kX)$. The force (tension) in the headgear strap F_s is given by the empirical equation $F_s = P(A_g - kX)/(2\cos \theta)$, where k is the spring constant for the

elasticity of the gusset portion and X is the amount of travel of the mask shell toward the face. Figure 10 also shows X_p , the working travel range of the gusset portion 32, although in practice, if the pressure in the mask pushes the face-contacting portion 34 away from the shell 20, X_p can be longer than is shown when the gusset is at rest.

5 Although k is usually not affected by pressure with respect to a purely mechanical spring, it has been found that within the pressure ranges occurring in the mask of the present invention, that k is proportional to both pressure and distance traveled. Thus, while in the present invention, the maximum force on the face F_m that could be expected to be exerted within X_p would be PA_g , testing has shown that this is reduced by the k factor which is both
10 proportional to pressure in the mask and distance traveled.

 For a prior art mask configuration, it is seen from Figure 1 that the force in the headgear strap $F_s = (F_c + PA_c)/(2\cos\theta)$. For the present invention mask, it is seen from Figure 10 that the force in the headgear strap $F_s = P(A_g - kX)/(2\cos\theta)$. The area defined by the gusset A_g is substantively larger than the area in contact with the face A_c . Therefore, at the point at which the cushion touches the face (the theoretical initial seal point when both $F_c = 0$ and $X = 0$), the force in the straps for the known mask will be $PA_c/(2\cos\theta)$ as opposed to $PA_g/(2\cos\theta)$ for the present invention mask. However, in reality, a contact force F_c greater than zero is required to: 1) maintain the seal between the face and the cushion because the profiles of the face and cushion are not perfectly matched, and 2) maintain this seal during movement of the
20 face relative to the shell. This force is balanced by the tension in the headgear straps in the known mask system and balanced by the pressure acting upon the gusset area alone, $A_g - A_c$, in the present invention mask system. Thus, within the normal operating mask air pressure range, and especially at lower operating mask air pressures, it has been found that the headgear tension F_s is lower in the present invention mask system.

From Figure 10, it can also be seen that for the present invention mask, the contact force between the cushion and the face is proportional to the mask pressure, $F_c = P(A_g - A_c - kX)$. This has significant implications in therapies where the mask air pressure varies during either the course of a breath or breath-to-breath or to meet other therapeutic needs. With known mask configurations, where the force of the cushion on the face varies little, if at all, with respect to the pressure in the mask, the tension in the straps must be set sufficiently high at low pressures such that the contact force of the cushion on the face is sufficient to maintain the seal with the face when higher pressures are reached.

For the present invention configuration, both the cushion contact force and the strap tension are significantly affected by the pressure in the mask due to the significantly increased area of the gusset. Therefore, as they both are most proportional to the pressure in the mask, they both will be significantly lower at low pressures and increase as the pressure reaches higher pressures.

In fact, in practice, it has been found that this holds true even at maximum mask air pressures. As an example, assume that A_c is the same in both a known mask (as, for instance, the ResMed Mirage® mask) and the inventive mask (both using, say, the same configuration in the face-contacting portion of the cushion). F_{Ac} would be the same in both cases. Then you might expect that given proper alignment of both masks, the minimum necessary F_c for sealing the masks at a given pressure would be the same in both the known and inventive masks and thus, the required F_m to seal at a given pressure to be the same in both cases. However, testing has shown that the present invention mask will seal at a lower force on the cushion, a lower force on the face, and a lower tension in the straps, even at the maximum mask air pressure, than the known mask. It is believed that the test results reflect the real world situation. That is, no face is identical and exactly conforms to the cushion and further, that it is extremely difficult to maintain exact alignment of the mask with the face. This is

even more the case with older and/or overweight patient that have loose skin, wrinkles and/or skin folds that hamper the sealing of the mask to the face. Testing has shown that the present invention mask is better able to accommodate these inconsistencies from user to user and provide better sealing performance at lower forces on the face (even at the maximum mask air pressure) than the known mask.

See also the chart in Figure 3 that shows a comparison of the present invention mask and known masks with respect to the force on the face as the mask shell moves toward the face. As long as the present invention is within the range X_p of the gusset, there is no sharp increase in the force on the face as with the known masks as the mask shell approaches the face. Beyond X_p , the force on the face will increase more dramatically, as happens with the known mask, so it is desirable when adjusting the headgear to bring the face contacting portion of the cushion only near or in very light contact with the face. In this way, the gusset is not compressed substantially so that in use the mask is still within the X_p range. This is possible because the seal is maintained by the pressure in the mask and not by compression of the cushion by the headgear. Adjustment of the headgear and mask is thus much simpler than in the known masks. While the range of X_p can be varied for different patients and therapies by varying the size and shape of the gusset section, it has been found that an X_p of between 10-30 mm has been effective. It is noted that the curves shown in Figure 3 are for a mask air pressure of 10 gf/cm^2 (grams force/centimeter²) These curves can be expected to rise and lower as the mask air pressure is increased and decreased, respectively, but will generally maintain the same shape within the operating pressure range of the mask.

In one embodiment of the present invention shown in Figures 4-9, the gusset and cushion are integrally molded of Silastic® 94-595 HC Liquid Silicone Rubber from Dow Corning®, the gusset sidewall 33 has a uniform thickness of 0.5 mm, the gusset has a long length (of the generally triangular A_g) of approximately 105 mm and the long length of the

generally triangular A_c is approximately 71 mm. The X_p is approximately 25 mm. Thus, the gusset (A_g) extends generally beyond the face-contacting portion of the cushion (A_c) by approximately 17 mm on each side. This provides for approximate figures for the A_c of 31.5 cm², the A_g of 75 cm², a gusset only area ($A_g - A_c$) of 43.5 cm² and an A_g/A_c of approximately 2.4 (or 240%). These dimensions can be altered for different force relationships as desired, but in the preferred embodiments, A_g/A_c will be in the range of about 1.30-5.00 and desirably in the progressively narrowing ranges of 1.50-5.00, 2.00-4.00, and 2.25-3.50, but can be adjusted to fall within any range within the overall range of 1.30-5.00 or even within a range extending beyond that range if circumstances warrant. This compares with an estimated A_g/A_c for the mask example disclosed in Japanese Provisional Publication No. 11-397 discussed above of approximately 1.08.

In the preferred embodiment of the mask, the total force applied to the face F_m is approximately constant at between 35 to 108 grams per gf/cm² mask air pressure, preferably between about 40 to 88 grams per gf/cm² mask air pressure and most preferably between about 50 to 88 grams per gf/cm² mask air pressure. The force applied by the surface area in contact with the face F_c is maintained at an approximately constant proportion to the mask air pressure being delivered to the user and is maintained between about 8 to 61 grams per gf/cm² mask air pressure, preferably between about 27 to 61 gms per gf/cm² mask air pressure and most preferably between about 40 to 61 grams per gf/cm² mask air pressure over a mask air pressure range of 4 to 25 gf/cm². The force F_c is also maintained within a range of about 0.3 – 4 grams per gf/cm² pressure of the supply of pressurized breathable gas per linear centimeter around a circumference of the cushion in contact with the user's face, preferably within a range of about 0.5 – 4 grams per gf/cm² pressure of the supply of pressurized breathable gas per linear centimeter around a circumference of the cushion in contact with the user's face, more preferably in a range of about 1 – 3 grams per gf/cm² pressure of the supply

of pressurized breathable gas per linear centimeter around a circumference of the cushion in contact with the user's face, and most preferably in a range of about 1.5 – 3 grams per gf/cm^2 pressure of the supply of pressurized breathable gas per linear centimeter around a circumference of the cushion in contact with the user's face over a mask air pressure range of 4 to 25 gf/cm^2 . Although the preferred force ranges for the various forces are set forth in this paragraph, it should be recognized that the force ranges can be set between any two points within the respective overall force ranges given. It is noted that in the industry of the present invention, most pressure measurements are given in centimeters water and that 1 centimeter water = $1 \text{ gf}/\text{cm}^2 = 98.07$ Pascals.

The gusset portion also allows the mask to maintain a seal with the patient's face over a range of about plus or minus 8° out of alignment with the patient's face.

It has also been found that the shape of the curve for the inventive mask shown in Figure 3 can be varied by altering the cross-section of the gusset or by providing a backstop for the gusset. Where the gusset has a very uniform thickness and curve, as shown in Figures 6 and 7, the curve for total force on the face versus movement of the mask toward the face will be generally linear within X_p . It has generally been found desirable in testing to apply a higher sealing force earlier as the mask shell travels toward X_p . That is, it is advantageous to move from C, the minimum force to seal at the given pressure, toward D, the minimum force for the inflated gusset, earlier in the travel of the mask shell toward X_p . This provides a greater remaining amount of X_p within which the mask will operate and a more gradual increase of the force of the mask on the face as the mask shell moves toward X_p within the remaining amount. The embodiments shown in Figures 12-14 help accomplish this goal.

In the first example, shown in Figure 12, the bases of the gusset sidewall are thickened in an abrupt manner to stiffen the sidewall. In this embodiment, the force-displacement curve for the mask generally follows the curve for the cushion (i.e., the curve

for the known mask shown in Figure 3) as it moves from C toward D and then a lower, generally linear slope until reaching X_p . See the long-dashed curve in Figure 3. However, changing the value for D can alter this curve. The value for D is calculated by multiplying the area for the stiffened portion of the gusset sidewall by the pressure in the mask. The stiffened portion of the gusset sidewall is shown as A_s in Figure 10. If however, the value of A_s is increased by stiffening a greater portion of the gusset sidewall, the value of D will increase. See the value for D' shown in Figure 3 and the short-dashed curve that corresponds to a mask embodiment where a greater portion of the gusset sidewall has been thickened (stiffened) to increase A_s . Thus, the long-dashed curve represents a gusset embodiment as shown in Figure 12 having an A_{s1} and the short-dashed curve represents a gusset embodiment as shown in Figure 12 having an A_{s2} greater than A_{s1} . It can be seen from Figure 3 that the gusset embodiment having the A_{s2} has reached the value D' much sooner as the mask shell moves toward X_p than the gusset embodiment having the A_{s1} , thereby leaving a greater remaining amount of the range X_p within which the mask shell can move in use.

A similar effect can be obtained by adding rigid backstops to the embodiment of Figures 6 and 7. See Figure 13, which shows an embodiment where rigid backstops 35 are attached to one or both of the gusset portion 32 and the shell 20. The rigid backstops contact the sidewalls of the gusset in the inflated mode and act as stiffeners to the portions of the sidewall that are contacted. Thus, the rigid backstops can provide the same effect as the embodiment of Figure 12. The backstops 35 can be placed on one or both sides of the gusset portion and can extend around either a portion, or all, of the perimeter of the gusset portion, as is necessary to provide the desired curve. The backstops can be made of the same material as the mask shell 20 and in one embodiment, one or both backstops 35 can be molded integrally with the shell 20. In alternative embodiments, the configurations shown in Figures 6, 7, 12, 14 and 16 can be used in combination with one another, i.e., one configuration on

one side of the gusset and another configuration on the other side of the gusset, to specifically tailor the force/travel curve as desired. The thicknesses and dimensions of the various embodiments can also be altered to specifically tailor the force/travel curve. This ability to readily and specifically tailor the force/travel curve of the mask by altering gusset configurations and dimensions is another unique and advantageous aspect of the present invention.

Where the gusset has sidewalls having a tapered thickness, as shown in Figure 14, the resulting force-displacement curve will lie between the curve for the embodiment of Figure 6 and the curve for the embodiment of Figure 12 (assuming comparable gusset base and intermediate thicknesses for the two embodiments).

The gusset portion need not be in the single gusset form discussed above, but can have alternative configurations, examples of which are shown in Figures 15-18, along with the A_c and A_g for each example.

Figure 15 shows an alternative embodiment of the mask 10 where the gusset portion 32 is in the form of a double gusset providing the decoupling joint between the face-contacting portion 34 of the cushion 30 and the mask shell 20. Of course, three or more gussets can be used in alternative embodiments of the gusset portion 32. Figure 16 shows an alternative embodiment of the mask 10 where the gusset portion 32 is in stepped form to provide the decoupling joint between the face-contacting portion 34 of the cushion 30 and the mask shell 20. While three steps are shown in Figure 16, one or more steps can be used in alternative embodiments. One advantage of this embodiment of gusset is the ease in molding the gusset portion 32 and cushion 30 together, since the shell side of the gusset portion 32 is completely open, i.e., there are no hidden surfaces. Figure 17 shows an alternative embodiment of the mask 10 where the gusset portion 32 is in the form of a piston 54 at the base of the cushion 30 axially slideably engaged with a cylinder portion 56 of the shell 20.

The piston 54 can thus move the cushion 30 in and out of the shell 20 to provide a decoupling joint between the face-contacting portion 34 of the cushion 30 and the mask shell 20. A stop 58 can be provided on the shell 20 to prevent the piston and cushion from completely disengaging with the shell 20 under pressure. A spring 60 can optionally be provided to push the piston 54 back into the shell 20 when the air pressure in the mask is decreased. The existence of the spring also simulates the elastic resistance of the gusset portions discussed above and adding a kX factor to the F_m equation. Without the spring, k would equal 0 within the range of movement of the piston.

Yet another alternative mask configuration is shown in Figure 18 which includes a gusset portion 32 having a larger upper barrel shaped gusset 78 and a lower smaller barrel shaped gusset 80. Alternatively, the larger and smaller gussets can be reversed, made the same size or even given different configurations to custom tailor the force characteristics.

Figure 21 shows an alternative embodiment of the mask of the present invention wherein the gusset portion 32 has a flexible sidewall 33 having a generally circular or round cross-section enclosing a gusset chamber 190 having an interior volume separated from an interior 192 of the mask shell 20. In one version of this embodiment the gusset chamber 190 can be connected to the mask shell interior 192 through at least one port 193 in the sidewall 33. See Figure 23. In such a case, a pressure P_2 in the gusset chamber will be the same as a pressure P_1 in the interior of the mask shell, the effective area of the gusset portion 32 A_g will extend to the outermost interior surface of the gusset sidewall 33, and the gusset portion will operate similarly to the embodiment shown in Figure 10. However, in a preferred version of this embodiment, the interior of the gusset chamber 190 is connected through a port in the sidewall 33 to a separate pressurized supply of gas than is connected to the mask shell interior so that the pressure P_2 in the gusset chamber 190 can be controlled to be at a different pressure than the pressure P_1 in the mask shell interior 192. Thus, the force imparted by the

gusset portion will be a product of the pressure P_2 and the area of the gusset portion. Further, in this embodiment, the area of the gusset portion is no longer determined by the outermost interior surface of the gusset sidewall as in the previous embodiments, but will be the projected area of the entire gusset chamber 190, including the area of the gusset chamber radially inward from the cushion sidewall. This area of the gusset chamber A_{gc} is shown in parentheses in Figure 21. This provides a high degree of flexibility in controlling the gusset portion and the mask.

First, if additional sealing force is needed from the gusset portion, the pressure P_2 can merely be increased, or vice-versa if less sealing force is needed. Second, since the force imparted on the cushion by the gusset portion is a product of the pressure P_2 and the area of the gusset portion A_{gc} , the area A_{gc} is less critical than in the previous embodiments because it can be offset by changes in the pressure P_2 . For instance, the outer periphery of the gusset portion can be made smaller in this embodiment than in the previous embodiments because an interior portion of the gusset portion is now also adding to the pressurized area of the gusset portion. Further, the area A_{gc} of the gusset chamber can be varied as desired, and especially made smaller, by varying the pressure P_2 . This allows the mask to be made smaller, as compared to the other masks discussed above, to be less intrusive and more comfortable to the patient.

The pressure P_2 can be controlled to be in relatively constant proportion to P_1 or can be controlled to be in varying proportion to P_1 as the circumstances warrant. While it is currently believed that in most therapies, P_2 will be greater than P_1 for most, if not all, of the therapy, it is contemplated that in certain situations, controlling P_2 to be less than P_1 can be desirable. In some instances, it is contemplated that P_2 be held constant. The gusset chamber in this embodiment is intended to be connected only to the second pressurized gas supply and otherwise be closed, especially to the atmosphere. Thus, there should be minimal leakage

from the gusset chamber and the second pressurized gas supply need only supply a small volume of gas, significantly less than the volume of gas that must be supplied for breathing purposes by the first pressurized gas supply. Further, the two separate pressurized gas supply sources for P_1 and P_2 can be provided by the same single gas pump and controlled by known control devices to be at the different desired pressures, or alternatively, two separate gas pumps can be used for the gas supplies to the mask interior 192 and the gusset chamber 190, respectively, to separately control each of P_1 and P_2 .

The gusset chamber 190 can be connected to the second gas supply through a port 194 in the gusset sidewall 33 connecting with a port 195 integrally molded with the mask shell 20 or can bypass the mask shell 20 and connect to the second gas supply through a port 196 in the gusset sidewall 33. See Figure 24, which shows both alternatives.

The embodiment of Figure 21 can have portions of the gusset sidewall 32 thickened/stiffened as discussed above with respect to Figures 12-14. However, the increased flexibility offered by controlling P_2 differently from P_1 means that the gusset sidewall can also be made generally uniform in thickness and a similar effect provided by the stiffening in the previously described embodiments can be provided in this embodiment merely by altering the pressure P_2 as desired.

In an alternative embodiment of the mask shown in Figure 21, the gusset portion 32 can have a generally diamond-shaped cross-section when the mask 10 is not in use or not pressurized, as shown in Figure 22, which cross-section can balloon to a generally circular cross-section when the gusset chamber is pressurized. Alternative shapes for the gusset portion 32 can also be used, including a piston/cylinder arrangement corresponding to Figure 17 discussed above.

The cushion can also have alternative configurations. See Figures 25-30, which show partial sectional views of the cushion 30. In each of these embodiments, the cushion 30 is

provided with a flexible membrane 170 that acts as a face-contacting portion 134. The flexible membrane 170 is attached to the more rigid supporting sidewall 173 of the cushion 30. These embodiments do not use an inner rim as does the embodiment shown in Figure 9. In each embodiment, the face-contacting portion 134 extends beyond an axially outer end 174 of the sidewall 173 when the cushion is at rest. The face-contacting portion 134 can move axially with respect to the sidewall 173 to alter an axial distance between the face-contacting portion 134 and the axially outer end 174. That is, when a force is applied to the cushion toward the users' face, the face-contacting portion 134 will retract, axially moving toward the axially outer end 174 of the sidewall 173. The axially outer end 174 of the sidewall 173 will provide a generally positive end limit to this retraction when it contacts the user's face.

In the embodiments shown in Figures 25 and 26, the flexible membrane 170 is attached to the sidewall 173 at a position 175 axially inward from the axially outer edge 174, with a portion of the flexible membrane 170 extending axially outwardly alongside the sidewall 173 between the position 175 and the axially outer edge 174. In these embodiments, axial movement of the face-contacting portion 134 is substantially provided by the flexibility of the flexible membrane 170. If a less rigid sidewall 173 is desired, for instance, to be more comfortable to the user when the axially outer edge 174 contacts the user's face, the sidewall 173 can have a hollow portion 176, especially between the position 175 and the axially outer edge 174. See Figure 26.

In the embodiments shown in Figures 27-30, the flexible membrane 170 is connected to the sidewall 173 by a flexible connecting member 177 that provides for axial movement between the flexible member 170 and the sidewall 173. The flexible connecting member 177 can have a generally straight cross-section, as seen in Figure 27, a convoluted cross-section, as seen in Figure 28, or another cross-section. The flexible connecting member 177 can be attached to the sidewall 173 near the axially outer end 174, as shown in Figures 27-29, or can

be attached to the sidewall 173 at an axially inward position 175, as shown in Figure 30. As with the embodiment of Figure 26, the sidewall can be at least partially hollow to make the sidewall less rigid. See Figure 29. In the preferred embodiment, the flexible membrane 170, the flexible connecting member 177 and the sidewall 173 are integrally molded together.

- 5 Although the flexible membrane is shown as being attached to a cushion sidewall, it is contemplated that in alternative embodiments, the flexible membrane can be attached directly to the mask shell, with a portion of the mask shell acting as the axially outer edge 174.

The embodiments of Figure 25-30 can be used in conjunction with the gusset feature described above or can be used with known mask cushions. These embodiments provide good sealing characteristics with the face in a cushion that is easier and less expensive to manufacture than the known mask cushions. It is also to be understood that in the embodiments of Figures 27-30, the flexible connecting member can act similarly to the gusset feature described above when the mask is pressurized. That is, the pressure in the mask will act on the flexible connecting member 177 to impart an additional force on the face-contacting portion 134 of the flexible membrane 170 and that additional force will have the same characteristics as described above with respect to the above-described embodiments. In the embodiments of Figures 27-30, the area A_c would be measured the same as in the embodiments above and the area A_g would be measured to the interior surface of the sidewall 173 where the flexible connecting member 177 attaches to the sidewall 173.

- 20 Other alternative embodiments can use various combinations of any of the embodiments disclosed herein.

It should be recognized that the gusset portion of the present invention can be manufactured as a component separate from the cushion and mask shell but is attachable therebetween to provide the benefits described herein.

The reduced contact force, total force on the face and headgear tension across the mask air pressure range and especially at mask air pressures below the maximum mask air pressure improves patient comfort, in particular for auto-titrating devices which start therapy at low pressures at the beginning of the night when the patient is trying to get to sleep. The improved seal (which can be obtained with a lower contact force) reduces sleep disturbance to patients and partners by substantially reducing the risk of leaks. The improved seal also increases the confidence of the patient in the seal, resulting in more comfortable therapy for the patient. See Figure 19, which diagrams how the key characteristics of the gusset portion of the present invention mask provide principal advantages leading to patient benefits and improved compliance with a prescribed therapy.

Another aspect of the present invention is the inclusion of the baffle 23 in the mask shell 20. The employment of the baffle in the mask shell 20 improves the movement of air within the mask. In the embodiment shown in Figures 4, 5 and 20, the baffle 23 is in the form of a flat plate disposed between the mask intake 22 and the mask exhaust vent 21. The baffle 23 can extend into the mask generally horizontally or can tilt upward or downward. The baffle need not be in the form of a flat plate but can be V-shaped, curved, wavy or have some other configuration best designed to deflect air from the intake from directly flowing to the exhaust vent. The baffle 23 can be integrally molded with the mask shell or attached to the shell by other known methods, including adhesive or ultrasonic bonding. It should be understood that the mask shell incorporating the baffle can be used in combination with the gusset portion, but that either of these aspects can be used alone in a mask of the present invention.

While the invention has been described in accordance with what is presently believed to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments but on the contrary, is intended to cover

